Product group: READY2COOK®

Description: RECT.700ML.HANDLES.BLACK

Item number: 0065112200

Restrictions: AVOID DIRECT CONTACT WITH

STRONGLY ACIDIC OR SALTY

FOOD

Product Specifications

| Shape | RECTANGULAR |
|----------------|----------------------------|
| Compartment | 1-COMPARTMENT |
| Closing option | SEALABLE |
| Application | FREEZER / MICROWAVE / OVEN |

| Volume | 700 ml |
|----------------------|--------|
| Capacity/compartment | 700 ml |
| Top out length | 234 mm |
| Top out width | 138 mm |
| Top in length | 218 mm |
| Top in width | 122 mm |
| Base length | 208 mm |
| Base width | 112 mm |
| Height | 30 mm |

Material Specifications

| Material | ALU COATED 1 |
|------------------|----------------------|
| Mono-material | YES |
| Color (in/out) | ALUMINIUM / BLACK |
| Recycled content | avg. 38% * |
| Foil description | LACQUER ³ |



Temperature

| Inside temp. Min | -40°C |
|-------------------|-------|
| Inside temp. Max | 350°C |
| Outside temp. Min | -40°C |
| Outside temp. Max | 200°C |

Packaging Specifications

| 0 0 . | |
|----------------------------|-----------------------------|
| Quantity/bag | 120 (+/- 2%) ² |
| Quantity/crt. | 480 (+/- 2%) ² |
| Quantity/pal. | 17280 (+/- 2%) ² |
| EAN-code bag | 5701022205484 |
| EAN-code crt. | 5701022205477 |
| EAN-code pal. | 5701022205491 |
| Weight/1 pc. | 13.775 g (+/- 10%) |
| Weight/1000 pcs. | 13.8 kg |
| Weight/crt. | 7.2 kg |
| Weight/pal. (excl. pallet) | 259.8 kg |
| Volume/crt. | 0.046 m3 |
| Size/crt. | 40 * 40 * 29 cm |
| Size/pal. (height) | 189 cm |
| Cartons/pal. | 36 |
| Cartons/layer | 6 |
| Layers/pal. | 6 |
| | |

¹ This product is made of a valuable material. Please recycle where possible.

The aluminium foil contains a food approved lubricate, the amount is depending on the shape and complexity of the container.

Matching Item

5021100203



² The number of packagings may vary, but the number is equalized by the total order.

³ Be aware that containers with outside and/or inside lacquer can have limitations on the specified temperature. Lacquer is specified to app. 200°C, but time, food and other conditions may affect heat resistance, therefore it must be tested at the customer. For more information on specific food stuffs, see relevant DOC.

^{*}The recycled content in % is the secondary production aluminium part. This is a calculated average based on raw material supplier data for the last 2 calendar years. It can be subject to changes based on changes from our supplier.