

Worksafe U-Damp

Hörselproppar på bygel med unika ovalformade proppar som garanterar komfortabel passform.

- Bygelns stabilitet begränsar kontakten med kläderna och därmed ljudöverföring till öronen
- Väger bara 8 g
- Idealiska för korttidsanvändning, t.ex. vid passage genom bullriga lokaler eller för besökare
- Lägre miljöbelastning då propparna kan bytas ut




Art nr	Beskrivning	Färg
40210864	U-Damp bygelpropp 1 st/frp	Svart
40210865	U-Damp utbytespropp 5 par/frp	Gul





U-Damp



European Standard EN 352-2

Attenuation data

H: 27 dB M: 19 dB L: 18 dB

SNR: 24 dB

1. Frequency Hz	63	125	250	500	1000	2000	4000	8000
2. Mean Attenuation dB	23.7	22.0	21.6	19.0	23.8	31.9	39.6	39.6
3. Standard Deviation dB	4.0	2.9	4.7	4.3	3.6	4.0	2.7	3.7
4. Assumed Protection dB (APV)	19.7	19.1	16.9	14.7	20.2	27.9	36.9	35.9

Sizes range: Small/Medium/Large
Größenbereiche: Klein/Mittel/Groß
Taille: Petite/Moyenne/Grande
Acc. to EN 352-2:1993

1. Frequenz Hz / Fréquence Hz
2. Mittlere Dämmung dB / Atténuation moyenne dB
3. Standardabweichung dB / Ecart type dB
4. Angenommene Schutzwirkung dB / Protection effective en dB

CE
EN 352

FITTING INSTRUCTIONS

Ensure correct seal and fit by carefully follow the instructions below:

1. Hold the band under your chin, with earplugs pointing forward. Fit plugs over ear canal entries with band under the chin.
2. Adjust the fit by pushing the band and plug gently with a slight rocking and twisting, at the same time as you pull the outer ear upwards/backwards with your free hand. Adjust opposite side accordingly.

NOTE:

- These banded earplugs are designed for wearing mode "under-the-chin" only.
- Band shall be worn with earplugs pointing forward only.
- Do not roll/compress plugs before fitting.

Made in Sweden

