



IPC

BY TENNANT COMPANY

SCRUBBER DRIERS - WALK BEHIND



CT40 MK2

MAX
PRODUCTIVITY

1750 m²/h

BATTERIES RUNNING
TIME

2,4 h


WATER TANK
RUNNING TIME

60'
Working session




MOST FREQUENTLY USE

RETAIL




HORECA



CLEANING CONTRACTORS



MUNICIPALITIES



INNOVATIONS



SLS
SELF
LEVELING
SYSTEM

SPECS



INTUITIVE OPERATION WITH
START-STOP PUSH BUTTON
CONTROL AND BATTERY
METER DISPLAY



EXCELLENT WATER PICK-
UP FEATURING AN EASILY
ADJUSTABLE SQUEEGEE
DESIGN WITH STANDARD
LINATEX BLADES



SIMPLE BRUSH/PAD CHANGE
OUT SYSTEM

TECHNICAL DATA

		CT40 MK2 B50	CT40 MK2 BT50
Code without batteries and charger		LPTB03862	LPTB03866
Code batteries and charger included		LPTB03864	LPTB03868
PERFORMANCE			
Max theoretical productivity	m ² /h	1500	1750
Cleaning path	mm	500	500
Water tank capacity (solution recovery)	l	42/42,5	42/42,5
Max running time	min	150	130
Voltage	V-Ah	24[2x12]-105 GEL	24[2x12]-105 GEL
Installed power	W	940	1060
Brush pressure	kg	21.5	21.5
Squeegee width	mm	784	784
Max speed	km/h	3	3.5
Weight (Without Batteries)	kg	67.5	86
Dimension (LxWxH)	mm	1294x784x1028	1294x784x1028

STANDARD ACCESSORIES

	CT40 MK2 B50	CT40 MK2 BT50
BRUSHES		
PPL	SPPV01332	SPPV01332
SQUEEGEE BLADES		
LINATEX FRONT BLADE	MPVR13667 - 788 mm	MPVR13667 - 788 mm
LINATEX REAR BLADE	MPVR13666 - 836 mm	MPVR13666 - 836 mm

CONSUMABLES (Codes available on price list)



OPTIONAL ACCESSORIES



BATTERIES AND BATTERY CHARGERS

BATTERIES	N°	CHARACTERISTICS	DIMENSION	RUNNING TIME	BATTERY CHARGERS
IPC gel battery BAAC00105	2	12V 105 Ah [C5]	345x170x285	150 min	On board battery charger 24V 15 Ah - KTRI07046 Stand alone high frequency BLS010 - BACA00133
EXIDE gel battery BAAC00024	2	12V 105 Ah [C5]	345x174x283	150 min	On board battery charger 24V 15 Ah - KTRI07046 Stand alone high frequency BLS010 - BACA00133
Acid tubular plate BAAC00136	2	12V 85 Ah [C5]	308x175x225	160 min	On board battery charger 24V 15 Ah - KTRI07046 Stand alone high frequency BLS010 - BACA00133 Stand alone low frequency 24V 12 Ah - BACA00060
Dry charge flate plate BAAC00009	2	12V 105 Ah [C5]	261x171x210	160 min	On board battery charger 24V 15 Ah - KTRI07046 Stand alone high frequency BLS010 - BACA00133 Stand alone low frequency 24V 12 Ah - BACA00060
Acid tubular plate BAAC00070	2	12V 118 Ah [C5]	345x170x285	160 min	On board battery charger 24V 15 Ah - KTRI07046 Stand alone high frequency BLS010 - BACA00133 Stand alone low frequency 24V 12 Ah - BACA00060

RECOMMENDED BATTERIES AND BATTERY CHARGER